

HEAT CALCULATOR

Model 212



Overview

The 212 Heat Calculator is designed to measure the energy consumed in hot water heating systems and chilled water cooling systems.

The 212 is supplied complete with temperature probes and will interface with a wide range of flowmeters, including positive displacement and inferential water meters, magnetic flowmeters with pulse outputs, turbine and paddle wheel flowmeters.

Provides Flexibility to Meet All Applications

The 212 is able to cross international boundaries in heat meter applications.

Multilingual capability datalogging and peak / off-peak operation are standard. In addition, four modes of operation covering heating and cooling ensure that the 212 is flexible enough to meet all energy measurement applications.

The high accuracy of the 212 ensures that it meets European and International approvals for heat calculators.

Accuracy to OIML R75 Class 4 and EN1434

The 212 can be supplied with two precision 4-wire Pt100 RTDs and has inbuilt correction for the non-linearity of the RTDs. For chilled water measurement where the temperature difference (Δt) is likely to be small, provision is made in the set-up program to zero out any offset between RTDs.

The 212 is fully programmable and all set-up data and totals are stored in a non-volatile memory for a minimum of 10 years.

Watertight Wall or Panel Mount Enclosure

The 212 Heat Calculator is housed in a rugged yet attractive IP66 (Nema 4X) rated polycarbonate enclosure which is completely watertight.

Mounting is either by a wall bracket or by panel mount.

Integration with Energy Management Systems

A Meter-bus interface enables the 212 Heat Calculator to be incorporated into energy management systems complying with European IEC 870-5 protocol standards.

The 212 is also supplied with an RS485 bus, which uses industry standard Modbus RTU protocol, for interfacing to computers and DCS systems.

Datalogging Flexibility

The 212 Heat Calculator will store energy totals by hour, day, week or month for up to 31 periods. The totals are stored for each period and can be downloaded to a computer via the Meter-bus or RS485 communications ports.

Peak and Off-peak Registers

If selected, the peak / off-peak feature will assign two separate registers which will totalise peak energy and off-peak energy.

The changeover times between peak and off-peak are fully programmable.

4-20 mA Output

A 4-20 mA output option is available and can be programmed to output flow rate, energy flow rate, feed or return temperature or Δt .

Note that the high and low alarms are not available if the 4-20 mA option is installed.

Modes of Operation

The 212 Heat Calculator is flexible enough to handle a wide range of applications. Four operating modes are available.

- Heating Mode where positive Δt 's only are totalised.
- Cooling Mode where negative Δt 's only are totalised.
- Heating / Cooling Mode where the flow of energy may be for heating or cooling. In this mode the energy total is increased regardless of whether Δt is positive or negative.
- Charge / Discharge Mode where two separate registers totalise positive and negative totals.

Specifications Model 212

General

Display	
Type	7 digit LCD - 7 numeric digits and 11 alpha characters
Digits	15.5mm (0.6") high
Characters	6mm (0.24") high
Display Units	kWh, MWh, MJ, GJ, therm, BTU x 1000, tons x hours (refrigeration)
Maximum Thermal Power	3000MW
Measurement Time	0.5s
Accuracy	OIML R75 Class 4 and EN1434
Approvals	Approved by Swiss Federal Office of Metrology to OIML Class 4
Interference	CE Compliance
Power Requirements	
dc Power	12 to 24V dc @ 100mA maximum
ac Power	Supplied via power adaptor

Physical

Temperature	
Operating	5 to 55°C
Storage	-20 to 70°C
Environmental Class	EN1434 Classes A & C
Enclosure	
Protection	IP66 (Nema 4X) watertight
Materials	Polycarbonate and ABS
Mounting Options	
Wall	Wall mount bracket
Panel	Mounting clips

Input

Flowmeter	
Type	Frequency or pulse between 0.01Hz to 20KHz Default low frequency cutoff is 0.25Hz
K-factor Range	Programmable in the range 0.001 to 999,999.9 pulses per litre, m3, US gallon or ft3
Signal Type	Pulse, open collector, reed switch, proximity switch or coil
Location	In either the return or feed lines
Temperature	
Type	4-wire Pt100 RTD's to IEC 751. 1/10 DIN
Location	1 x Feed Line and 1 x Return Line
Linearisation	Built-in RTD linearisation
Temp Range	-10 to 220°C (1 to 200°C approved)
Temp Difference	1 to 200K (3 to 199K approved)
Measurement Time	3s
Cable Length	<50m
Connection	G1/2B

Outputs

Pulse	
Type	Open collector will sink up to 100mA, 30V dc maximum
Width	10ms
Function	Volume or Energy (scaled)
Frequency	1 pulse every preset number of units of energy or volume total
Alarm (Not available with 4-20mA output)	
Type	Two solid state opto-isolated relays which will sink up to 100mA, 30V dc maximum
Function	High and low alarms individually programmable as unsigned values for flow rate, energy flow rate, feed temperature, return temperature or temperature difference
4-20mA Output Option	
Function	Volumetric flow rate, energy flow rate, feed or return temperature, Δt
Accuracy	0.1%
Span	Programmable
Load	Maximum of 300 ohms at 12V
Meter-Bus	
Type	Conforms to CEN/TC176 Meter-bus standard
Protocol	IEC 870-5.
RS485	
Data Transmitted	All data calculated can be transmitted
Baud Rate	300 to 9600 baud
Parity	Odd, even or none
Stop Bits	One or two
Bus Address	Programmable for multiple instruments on the same bus
Protocol	Modbus RTU

Important: Specifications are subject to change without notice.

Product Codes

212	.					Heat Calculator
Enclosure And Mounting	0	1	2			Wall Mounting (no gland holes) Panel Mount Wall Mounting (Standard glands)
Output Option	0	1				No Option 4-20mA
Power Option				N E U A H		DC Powered European Adapter (220 vac) UK Adaptor (100Vac) USA Adaptor (100 Vac) Australian Adaptor
Temperature Sensor					8 1 2	No Probe 85mm insertion 120mm insertion 210mm insertion
Approvals					S	OIML R75 Compliant No Approvals

Typical Part Number: 212.20E1S

Terminal Descriptions

RTD Connections		Flowmeter Signals		Communications		Alarm Relays		Power Supply	
No.		No.		No.		No.		No.	
1	High temp RTD Current (+)	9	Namur Switch (+)	24	Meter-Bus	52	Relay 0 (+) dc voltage only	50	12V dc Supply (+)
2	High temp RTD Current (-)	10	Flow Signal Input	25	Meter-Bus	53	Relay 0 (-) dc voltage only	51	12V dc Supply (-)
3	Low temp RTD Current (+)	11	Coil Reference			54	Relay 1 (+) dc voltage only		
4	Low temp RTD Current (-)	12	Flow Signal Common	56	RS485 (+)	55	Relay 1 (-) dc voltage only	58	Shields
5	High temp RTD Input (+)			57	RS485 (-)				
6	High temp RTD Input (-)								
7	High temp RTD Input (+)	16	Pulse Output (+)			4-20mA Output			
8	High temp RTD Input (-)	17	Pulse Output (-)			52	4-20mA (+)		
						53	4-20mA (-)		

Dimension Drawings

