

BATCH CONTROLLER

Model 214D



Overview

The Model 214D Batch Controller is designed for flow applications where the precise control of batch quantities is required. Batch Total, Accumulated Total and Preset values can all be displayed on the large LCD display.

For hazardous area applications, the 214Di is an intrinsically safe version with both ATEX approval, and CSA approval covering both the USA and Canada.

The 214D has an input conditioning circuit which will accept pulse or frequency flow signals generated by turbine, positive displacement, paddlewheel or other flowmeters.

Configurable link positions enable the input circuit to be configured for the different signal types.

DC Powered with Battery Backup

The 214D will operate from an external power source between 9 and 28 Volts and draws no more than 4 mA.

Lithium batteries provide backup if the DC power is interrupted so that totals are not lost. The solenoids or sensors, however, may still require external power.

Solid state outputs provide control to solenoids and relays, and can sink up to 200 mA.

Watertight Field Mounting Enclosure

The 214D Rate Totaliser is housed in a rugged yet attractive IP67 (Nema 4X) rated polycarbonate enclosure which is completely watertight.

A special universal bracket, supplied as standard, enables the instrument to be wall mounted. A 2" pipe mounting bracket is also available as are bottom and rear mounting stems for mounting the 214D directly on turbine flowmeters which have a 1" NPT or BSP boss.

Intrinsically Safe Installation

The 214Di is certified for use in hazardous areas with approved sensors and solenoids, according to the following approvals.

Flowmeters with Namur Proximity Switches

Namur Proximity switches may be used but will require a separate barrier to power the Namur switch, as shown opposite.

Fully User Programmable

K-factor, decimal point positions, valve delays and signal timeouts are fully user programmable.


The Signal Timeout feature, if programmed, will automatically stop the batch if the flow signal cuts out midway through a batch.

One or Two Stage Valve Control

Two solid state relays are provided which can be set up to control a single or a two stage valve with slow stop and / or slow start. Alternatively, the second output can be used to control a pump. The first output will energise at the start of the batch, and de-energise when the batch is complete. The second output can be programmed to energise at a delayed Staid Time after the batch start (0 to 9 seconds delay), and to de-energise at a Prestop quantity prior to completion of the batch. This feature enables a slow startup and slow shutdown of the flow.

Keyboard Operation

The unique 3 key operation of the 214D simplifies operation and enables batches to be controlled quickly and efficiently.



214D Facia

To enter a batch, the PRESET key is pressed and the ► and ▲ keys can be used to increment and change digits. Once set, the PRESET key is pressed again to return to the run mode.

In the run mode, the RUN and STOP keys are used to start, stop or to pause the batch.

ATEX

Approval: DMT 03 ATEX E 097
Type of Protection: 11 2G EEx ia IIB T3

CSA_{US/C}

Approval: 104840-5
Locations: Class 1, Groups C & D
Temperature: Maximum ambient of 60°C

Flowmeter Input

The 214Di will connect directly to a turbine or paddlewheel with a certified IS coil or other certified IS devices which produce a pulse output, provided they do not produce a voltage, current or power which exceeds:

$$U_i = 24V, I_i = 20 \text{ mA}, P_i = 320 \text{ mW}$$

The maximum allowed capacitance and inductance of the pulser or coil, including cabling is limited to:

$$C_{ext} = 60\mu F, L_{ext} = 1.5H$$

Output parameters on the input are:

$$U_o = 10.0V, I_o = 9.0 \text{ mA}$$

Note that devices such as reed switches, which can be classed as "Simple Apparatus" as defined in EN50020, may be connected to the 214Di without additional certification.

Output and DC Power

A barrier is required to provide DC power to the instrument and to power the IS solenoids or relays. One or two barriers may be used depending upon whether a one or two stage valve is used. Connection is as shown opposite.

Only certified intrinsically safe solenoids may be used for IS applications. Because these solenoids have a relatively small coil, they are usually only suitable for small line sizes and non-viscous product.

Generally, it is preferable to use a pneumatic system with the solenoid valves controlling air to a larger pneumatically controlled valve.

BATCH CONTROLLER

Specifications Model 214D

General

Display	
Batch Total	7 digit 10mm (0.4") high LCD (continuously powered) Note: The Accumulated Total is displayed when the ACCUMTOT key is pressed
Preset	5 digit 8.5mm (0.33") high LCD (continuously powered)
K-factor Range	The pulses per unit of measure (eg. Pulses / gallon) is programmable in the range of 0.0001 to 999,999
Dicimal Points	Fully programmable for Total
Frequency Range	0Hz to 10kHz
Signal Type	Link settable for sine wave (15mV P-P minimum), open collector, reed switch or pulse
Interference	CE compliance
DC Power Input	9-28V @ 4mA maximum

Battery Backup

Type	2 x Lithium battery packs.
Function	The batteries will provide backup power for the instrument if no DC power is available. The batteries will not power the sensor (if power is required) or solenoid outputs

Product Codes

214D	.	3	Batch Calculator
Intrinsic Safety	i		Intrinsically safe Not intrinsically safe
Enclosure and Mounting	0		Wall Mounting (no gland holes)
	1		Panel Mount
	2		Wall Mounting (Standard glands)
	3		Explosionproof Enclosure (USA Only)
	4		Turbine Mount (bottom)
	5		Turbine Mount (rear)
	6		Pipe Mount
Output (Standard)		3	DC Powered
Hazardous Approvals	C		CSA US & Canadian Approval
	M		ATEX Approval
	S		SAA Australian Approval
			No Approvals

Typical Part Numbers: 214Di.23M or 214D.13

Important: Specifications are subject to change without notice

Physical

Operating Temp.	-20 to 60°C
Enclosure	
Protection	IP67 (Nema 4X) watertight
Cable Entry	By cable glands
Materials	Polycarbonate and ABS
Mounting Options	
Wall	Wall mount bracket.
Pipe	A galvanised metal bracket enables the 214D to be attached to a 2" vertical or horizontal pipe
Panel	Two mounting brackets supplied
Turbine Meter	Bottom and rear mounting stems are available for mounting the 214D directly on turbine flowmeters which have a 1" NPT or BSP boss

Outputs


Type	2 x solid state relay outputs suitable for driving DC solenoids or external relays. The outputs provide for one or two stage control for the flow
Switching Power	200mA, 30V dc maximum
Saturation Voltage	0.8V dc across output when in the "on" state
Isolation	Both outputs are separately Isolated

Terminal Descriptions


Number		Number	
1	DC Power Input 0V	5	Output 2 (-)
2	DC Power Input 9-28V	6	Output 2 (+)
3	Output 1 (-)	7	Pulse/Coil Input (-)
4	Output 1 (+)	8	Pulse/Coil Input (+)

Dimensional Diagrams


Flowmeter Mount



Wall Mount



Panel Mount



Pipe Mount Adaptor

