


P Series

Feature

- Safety standard : UL, CSA, TUV
- World wide input voltage range
 - AC85~264V free voltage (15, 30W)
 - AC85~132V / 170~264V selectable or automatic selection (50~1,500W)
- Inrush current, overcurrent and overvoltage protection
- Parallel operation, master-slave operation, and remote control function (300, 600, 1,500W)

3-year warranty



P15, P30, P50, P100, P150, P300, P600, P1500, PT1500

Model (W)	Input (V)	Output (V)	Output (A)	Size · Weight W · H · D (g)	Safety Standard	Remark	
P15E (15W)	AC85 ~ 264 DC110 ~ 370	5	3.0	35 · 97 · 99.5 (300)			
		9	1.7				
		12	1.3				
		15	1.0				
		18	0.9				
		24	0.7				
		30	0.5				
48		0.35					
P30E (30W)		AC85 ~ 264 DC110 ~ 370	5	6.0	35 · 97 · 124.5 (400)		
			9	3.4			
			12	2.5			
			15	2.0			
			18	1.7			
			24	1.3			
	30		1.0				
48	0.63						
P50E (50W)	AC85 ~ 264 DC110 ~ 370		5	10.0	37 · 97 · 160 (400)		
			9	5.5			
			12	4.2			
			15	3.4			
			18	2.8			
			24	2.1			
		30	1.7				
48		1.0					
P100E (100W)		AC85 ~ 264 DC110 ~ 370	5	20.0	50 · 93 · 189 (700)		
			9	11.2			
			12	8.5			
			15	7.0			
			18	5.6			
			24	4.5			
	30		3.3				
48	2.1						
P150E (150W)	AC85 ~ 132 AC170 ~ 264 DC220 ~ 370		5	30.0	65 · 93 · 199 (900)		
			9	16.7			
			12	13.0			
			15	10.0			
			18	8.4			
			24	6.5			
		30	5.0				
48		3.3					
P300E (300W)		AC85 ~ 132 AC170 ~ 264 DC220 ~ 370	5	60.0	120 · 93 · 190 (2.5k)		
			12	27.0			
			15	22.0			
			18	17.0			
			24	14.0			
			30	10.0			
	48		6.5				
P600E (600W)	AC85 ~ 132 AC170 ~ 264 DC220 ~ 370		5	120.0	190 · 93 · 200 (4.0k)		
			12	53.0			
			15	43.0			
			18	34.0			
			24	27.0			
			30	20.0			
			48	13.0			
P1500E (1500W)		AC85 ~ 132 AC170 ~ 264 DC220 ~ 370	5	300.0	200 · 97 · 300 (7.0k)		
			9	167.0			
			12	125.0			
			15	100.0			
			18	84.0			
			24	65.0			
			30	50.0			
48	32.0						
PT1500U (1500W)	AV170 ~ 264 (3Ø)		5	300.0	200 · 97 · 300 (7.6k)		
			24	65.0			