

(CO NO.: 274734-P)



No.42, Jalan Kuchai Maju 11, Kuchai Entrepreneur Park, Jalan Kuchai Lama, 58200, Kuala Lumpur, Malaysia. Tel: +603 7980 0808 Fax: +603 7980 0202 www.dpcontrols.com.my



RTD Probes with Hex Nipple

A1RTD1-HXXL01-01



Overview

- All temperature sensors are custom made standard item
 - 100 ohm platinum RTD 3-wire element
 - Class A accuracy
 - Ø6.35mm diameter, 316 SS sealed stainless steelsheath to protect against harsh environments
 - RTD element encased in Magnesium Oxide (MgO) powder insulation provides excellent vibration dampening and heat transfer
 - 150mm, 300mm, 450mm probe length
 - 1/2" x1/2"BSP hex nipple allows easy replacement of existing probes and connection to a wiring junction box
 - Others
 - Required others type of RTD sensor ,specification & temperature range can be custom made upon request.

RTD Probes with Hex Nipple						
Part Number	RTD Type	Probe Diameter (O.D)	Probe Length	Temperature Sensing Range	Mounting	
A1RTD1-H06L01-01			150mm			
A1RTD1-H12L01-01	PT-100	6.35mm	300mm	-200 to 300°c	Integral 1/2" x 1/2" BSP	
A1RTD1-H18L01-01	3 wire		450mm		304 SS	

Technical Specifications				
Sensing Element Single 100 ohm platinum (PT 100), 3 wire				
Initial Accuracy	Class A +/- [0.15 + 0.002 ltl] ° C			
Probe	Ø6.35mm ,316 stainless steel sheath,single RTD is embedded in MgO powder			
Minimum Installation Depth	(76mm)			
Wiring	76mm stranded 24WG wire leads ,teflon insulated			

Dimension

A1RTD1-HXXL01-01




TABLE A				
PART NUMBER	U LENGTH			
A1RTD1-H06L01-01	150mm			
A1RTD1-H12L01-01	300mm			
A1RTD1-H18L01-01	450mm			

Wiring Information

